

TC808B Series

Intelligent Thermal (Heat) Detectors with FlashScan®

General

Honeywell TC808B Series intelligent plug-in thermal detectors with integral communication has features that surpass conventional detectors. Point ID capability allows each detector's address to be set with decade address switches, providing exact detector locations. TC808B Series thermal detectors use an innovative thermistor sensing circuit to produce 135°F/57°C fixed-temperature (TC808B1041) and rate-of-rise thermal detection (TC808B1058) in a low-profile package. TC808B1066 provides fixed high-temperature detection at 190°F/88°C. These thermal detectors provide effective, intelligent property protection in a variety of applications. TC808 Series detectors are compatible with the Honeywell Fire Alarm Control Panels (FACPs).

FlashScan® (U.S. Patent 5,539,389) is a communication protocol that greatly enhances the speed of communication between analog intelligent devices. Intelligent devices communicate in a grouped fashion. If one of the devices within the group has new information, the panel's CPU stops the group poll and concentrates on single points. The net effect is response speed greater than five times that of earlier designs.

Features

- Sleek, low-profile, stylish design.
- State-of-the-art thermistor technology for fast response.
- Rate-of-rise model (TC808B1058), 15°F (8.3°C) per minute.
- Factory preset at 135°F (57°C); high-temperature model at 190°F (88°C).
- Addressable by device.
- Compatible with FlashScan® and CLIP protocol systems.
- Direct dial entry of address 01-159 for FlashScan® loops, 01-99 CLIP mode loops.
- Two-wire SLC connection.
- Visible LEDs "blink" every time the unit is addressed.
- 360°-field viewing angle of the visual alarm indicators (two bi-color LEDs). LEDs blink green in Normal condition and turn on steady red in Alarm.
- Integral communications and built-in device-type identification.
- Remote test feature from the panel.
- Built-in functional test switch activated by external magnet.
- Walk test with address display (an address of 121 will blink the detector LED 12-(pause)-1).
- Low standby current.
- Backward-compatible.
- Built-in tamper-resistant feature.
- Designed for direct-surface or electrical-box mounting.
- Sealed against back pressure.
- Plugs into separate base for ease of installation and maintenance. Separate base allows interchange of photoelectric, ionization and thermal sensors.
- SEMS screws for wiring of the separate base.
- Constructed of off-white Bayblend®, designed to commercial standards, and offers an attractive appearance.
- 94-5V plastic flammability rating.



TC808B Series in 14507371-001 base

- Remote LED output connection to optional RA400Z remote LED annunciator.
- Optional sounder, relay, and isolator bases.
- Optional recessed (RMK400) or surface (SMK400E) base mounting kits.

Specifications

Size: 2.1" (5.3 cm) high x 4.1" (10.4 cm) diameter installed in B501 base, 6.1" (15.5 cm) diameter installed in 14507371-001 base.

Shipping weight: 4.8 oz. (137 g).

Operating temperature range: TC808B Series, TC808B1058: -20°C to 38°C (-4°F to 100°F); TC808B1066: -20°C to 66°C (-4°F to 150°F).

Detector spacing: UL approved for 50 ft. (15.24 m) center to center. FM approved for 25 x 25 ft. (7.62 x 7.62 m) spacing.

Relative humidity: 10% – 93% noncondensing.

Thermal ratings: fixed-temperature setpoint 135°F (57°C), rate-of-rise detection 15°F (8.3°C) per minute, high temperature heat 190°F (88°C).

Altitude rating: 10,000 feet.

ELECTRICAL SPECIFICATIONS:

Voltage range: 15 - 32 volts DC peak.

Standby current (max. avg.): 300 µA @ 24 VDC (one communication every 5 seconds with LED enabled).

LED current (max.): 6.5 mA @ 24 VDC ("ON").

BASES AVAILABLE:

14507371-001: 6.1" (15.5 cm) diameter.

14506414-002: 4.1" (10.4 cm) diameter.

B501BH-2 or B501BHT-2: Sounder base assembly.

B224RB Relay Base: Screw terminals: up to 14 AWG (2.0 mm²). Relay type: Form-C. Rating: 2.0 A @ 30 VDC resistive; 0.3 A @ 110 VDC inductive; 1.0 A @ 30 VDC inductive. Dimensions: 6.2" (15.748 cm) x 1.2" (3.048 cm).

14507371-005 Isolator Base: Dimensions: 6.2" (15.748 cm) x 1.2" (3.048 cm). Maximum: 25 devices between isolator bases. See Note 2 under Installation.

Applications

Use thermal detectors for protection of property. For further information, go to systemsensor.com for manual I56-407-00, Applications Manual for System Smoke Detectors, which provides detailed information on detector spacing, placement, zoning, wiring, and special applications.

Installation

The TC808B Series plug-in intelligent thermal detector uses a separate base to simplify installation, service, and maintenance. Installation instructions are shipped with each detector.

Mount base (all base types) on an electrical backbox which is at least 1.5" (3.81 cm) deep. Suitable boxes include:

- 4.0" (10.16 cm) square box.
- 3.5" (8.89 cm) or 4.0" (10.16 cm) octagonal box.
- Single-gang box (except relay or isolator base).
- With B501BH-2 or B501BHT-2 base, use a 4.0" (10.16 cm) square box.
- With B224RB or 14507371-005 base, use a 3.5" (8.89 cm) or 4.0" (10.16 cm) octagonal box, or a 4.0" (10.16 cm) square box.

NOTE: 1) Because of the inherent supervision provided by the SLC loop, end-of-line resistors are not required. Wiring "T-taps" or branches are permitted for Style 4 (Class "B") wiring. 2) When using relay or sounder bases, consult 77-4555 (TC811A1006) for device limitations between isolator modules and isolator bases.

Agency Listings and Approvals

Listing information not available. Consult panel manuals for lists of compatible UL-Listed devices. In some cases, certain modules or applications may not be listed by certain approval agencies, or listing may be in process. *Consult factory for latest listing status.*

- **UL Listed:** S1196
- **ULC Listed:** S6972
- **FM Approved**
- **CSFM:** 7272-1130:144

Product Line Information

"A" or "CDN" suffix indicates ULC Listed model.

TC808B1041: Intelligent thermal detector fixed 135°F. Must be mounted to one of the bases listed below.

TC808B1041CDN: Same as TC808B1041 but with ULC Listing.

TC808B1058: Intelligent thermal detector with rate-of-rise feature.

TC808B1058CDN: Same as TC808B1058 but with ULC Listing.

TC808B1066: Intelligent high-temperature 194°F thermal detector.

TC808B1066CDN: Same as TC808B1066 but with ULC Listing.

BASES:

14507371-001BP: Standard flanged low-profile base, pkg. of 10.

14507371-001: Standard flanged low-profile base.

14507371-001CDN: Standard flanged low-profile base.

14506414-002BP: Standard flangeless base, pkg. of 10.

14506414-002: Standard flangeless base.

14506414-002CDN: Standard flangeless base, ULC Listing.

BH501BH-2: Sounder base, includes **14506414-002** base above.

BH501BHT-2: Same as B501BH-2, but includes temporal sounder.

BH501BHA: Sounder base, includes **14506414-002** base above

BH501BHTA: Same as BH501BHA, but includes temporal sounder.

14507371-005: Intelligent isolator base. Isolates SLC from loop shorts.

14507371-005CDN: Same as 14507371-005, but with ULC Listing.

ACCESSORIES:

F110: Retrofit replacement flange for older style high profile bases. Converts bases for use with FlashScan® detectors.

RA400Z: Remote LED annunciator. 3 – 32 VDC. Fits U.S. single-gang electrical box. Supported by 14507371-001(CDN) and 14506414-002(CDN) bases only.

SMK400E: Surface mounting kit provides for entry of surface wiring conduit. For use with 14506414-002(CDN) base only.

RMK400: Recessed mounting kit. For use with 14506414-002(CDN) base only.

SMB600: Surface mounting kit for use with 14507371-001(CDN).

BCK-200B: Black detector covers, box of 10.

M02-04-00: Test magnet.

M02-09-00: Test magnet with telescope stick.

XR2B: Detector removal tool. Allows installation and/or removal of FlashScan® Series detector heads from base in high ceiling installations.

T55-127-010: Detector removal tool without pole.

XP-4: Extension pole for XR2B. Comes in three 5-ft. sections.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

FlashScan® is a registered trademark of Honeywell International Inc. Bayblend® is a registered trademark of Bayer Corp. ©2009 by Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited.

Automation and Control Solutions

Honeywell International Inc.
1985 Douglas Drive North
Golden Valley, MN 55422
www.honeywell.com

Honeywell Limited-Honeywell Limitée
35 Dynamic Drive
Scarborough, Ontario M1V 4Z9

74-3354-1 Rev. 06-09
June 2009
Made in the U.S.A.
© U.S. Registered Trademark
© 2009 Honeywell International Inc.
Page 2 of 2



Honeywell